





**HI-LITE MFG.
CO., INC.**
13450 Monte Vista Avenue
Chino, California 91710
Telephone: (909) 465-1999
Fax: (909) 465-0907

Job Name: _____
Type: _____
Quantity: _____

Item Number	Height (A)	Width (B)
H-16007	6 1/4"	7"
H-16008	8"	8"
H-16110	10 1/4"	10"
H-16112	10 3/4"	12"
H-16114	14"	14"
H-16116	16 1/2"	16"
H-16118	17"	18"
H-17118	18"	19 1/2"
H-17124	20 1/4"	24"

Deep Bowl Collection



Fixture No.	Fixture Color	Mounting	Mounting Color	Optional Accessories	Accessory Color	Wattage/Lamp options	Ballast	Voltage
H-16007 (1)	Standard (2)	Mounting Options	Standard	CGU (Cast guard & glass)	Standard	Incandescent (7) (Fixture is standard 100W or 200W. Do not specify.)	Ballast option not available for INC.	Incandescent (Fixture is standard 120V. Do not specify.)
H-16008 (1)	91 (Black)	12"	91 (Black)	LCGU (Large cast guard & glass)	91 (Black)	CFL (4) (7) (Compact Fluorescent)	RB (5) (Remote)	CFL M (Multi 120/277V)
H-16110	93 (White)	3/4"	93 (White)	WGU (Wire guard & glass)	93 (White)	13/CFL	BCM (Canopy Mount)	HID RB and BCM
H-16112	95 (Dk. Grn)	Cord Options (3)	95 (Dk. Grn)	LWGU (Large wire guard & glass)	95 (Dk. Grn)	26/32/42/CFL	PLB (6) (Postline)	M (Multi 120/208/240/277V)
H-16114	96 (Galv.)	CB8 (8' Blk Cord)	96 (Galv.)	ARN (Acorn globe)	96 (Galv.)	26/CFL	For specs see pages 341-343.	PLB 1 (120V) 2 (277V)
H-16116 (2)	BR47 (Rust)	CW8 (8' Wht Cord)	BR47 (Rust)	LARN (Large acorn globe)	BR47 (Rust)	42/CFL		
H-16118 (2)	BK01, GN20.	CG8 (8' Gray Mesh Cord)	For all finishes see pages 344-348.	WGR (Wire guard)		57/CFL		
H-17118 (2)	Upgraded (2) Finishes.	Custom Cord Options (3)		SK (Swivel knuckle)		DMB (Dimmable Ballast for CFL. Add to Part No.)		
H-17124 (2)	29, 66, 82, 92, 94, 97, 100, 103, 104, 105, 112, 113, 114, 117, 118, 119, 127, 128, 133, 134, 135, 136, 98, 101, 102, 137, 139, 140, 121, 122, 123, 124, 11, 01, 22, 25, 33, 77, 89, 24, 44, 48, 49, 15, 16.	CB (Black) CW (White) CG (Gray Mesh) Specify length.		FX (Flexible tubing for cord mounted fixture only)		HID (4) (High Intensity Discharge)		
	For finish specs see pages 344-348.	Stem Options (Stem 1/2") ST Specify length and canopy. HSC (Canopy) SMC (Canopy)		For specs and glass color see pages 321-344.		MH (4) (7) (Metal Halide) 35/MH 50/MH 70/MH 100/MH 150/MH 175/MH		
		Flush Mount Options FHSC FSMC				HPS (4) (7) (High Pressure Sodium) 50/HPS 70/HPS 100/HPS 150/HPS		
		Arm Options B-1 HL-K HL-A HL-U HL-H P-1 HL-C P-3 HL-D				LED See LED specification sheet.	LED See specifications for complete part number.	LED See specifications for complete part number.
		For all arms and specs see pages 321-344.						

H-16007 - 91 / 1/2" - 91 / CGU-FR - 91 / 13/CFL - BCM - M

ORDER EXAMPLE
(USE THIS FORMAT TO PLACE ORDER)

Notes:

- (1) H-16007 and H-16008 available for 100W Max INC. H-16007 and H-16008 not available with glass enclosures.
- (2) For interior finish of fixture refer to color chart on pages 344-348. H-16116, H-16118, H-17118 and H-17124 not available in copper or brass finish.
- (3) Cord Mounting wattage not to exceed 100 for HID. Gray Mesh Cord not available for HID.
- (4) Requires Globe Option. (See pages 339-341 for Globe Options)
Max Wattages for CGU and WGU are 100W INC, 32W CFL and 100W HID.
Max Wattages for LWGU, LCGU, ARN and LARN are 200W INC, 57W CFL and 175W HID.
- (5) (RB) Remote Ballast not available for Fluorescent Lamping.
- (6) (PLB) Post Line Ballast must specify 120V or 277V. (PLB) 50W MH requires a 3" dia. pole. (PLB) 70W and 100W MH require a 4" dia. pole. (PLB) 50W, 70W, 100W and 150W HPS require a 3" dia. pole.
- (7) Socket Bases: INC and HID are medium base. CFL is GX24Q.

Cord-hung fixtures: suitable for dry location only.
Stem-hung fixtures: suitable for damp & dry location.
Gooseneck, post mount & wall bracket fixtures: suitable for wet, damp & dry location.